



LIGHT SADDLE



FEATURES AND BENEFITS.

Description:-	<ul style="list-style-type: none"> * It is recommended for supporting a piping system with vertically or horizontally to walls or ceilings. * Easy to install because of light weight. * Maximum temperature : 343°C (650°F).
Material:-	Steel, other materials on request.
Special:-	<ul style="list-style-type: none"> * Electro galvanized as per ASTM B 633. * Designed to meet MSS Standard SP-58, type 26 and SP-69.

Product Code	Nominal Pipe Size In.	Nominal Pipe Size mm	Pipe OD (D) mm	Hole Size (S) mm	Max Load (N)	Microns (μ)	Box Quantity
VTEPLS022	½"	DN15	21.3	M6.2	500	8-15	2000
VTEPLS027	¾"	DN20	26.7	M6.2	500	8-15	1750
VTEPLS034	1"	DN25	33.4	M6.2	500	8-15	1500
VTEPLS042	1¼"	DN32	42.1	M6.2	500	8-15	1250
VTEPLS048	1½"	DN40	48.2	M6.2	500	8-15	1000
VTEPLS060	2"	DN50	60.3	M6.2	500	8-15	800
VTEPLS073	1½"	DN65	73	M6.2	500	8-15	750
VTEPLS090	3"	DN80	88.9	M6.2	500	8-15	500
VTEPLS114	4"	DN100	114.3	M6.2	500	8-15	300

NOTE:- 1. OTHER DIMENSIONS AVAILABLE ON REQUEST.

