



HALF SADDLE



FEATURES AND BENEFITS.

Description:-	<ul style="list-style-type: none">* Recommended for support of standard conduit, cable and steel pipe on walls or sides of beams.* Not recommended for use horizontally on ceilings, bottoms safety of beams and similar installations since the factor of safety is greatly reduced when so used.* Maximum temperature : 343°C (650°F).
Material:-	Steel, other materials on request.
Special:-	<ul style="list-style-type: none">* Electro galvanized as per ASTM B 633.* Designed to meet MSS Standard SP-58, type 26 and SP-69.

Product Code	Nominal Pipe Size In.	Pipe OD (D) mm	Hole Size (S) mm	Max Load (N)	Microns (μ)	Box Quantity	
VTEPHS022	½"	DN15	21.3	M6.2	1250	8-15	2000
VTEPHS027	¾"	DN20	26.7	M6.2	1250	8-15	1600
VTEPHS034	1"	DN25	33.4	M6.2	1250	8-15	1200
VTEPHS042	1¼"	DN32	42.1	M6.2	1250	8-15	1000
VTEPHS048	1½"	DN40	48.2	M6.2	1250	8-15	800
VTEPHS060	2"	DN50	60.3	M6.2	1250	8-15	600

NOTE:- 1. OTHER DIMENSIONS AVAILABLE ON REQUEST.